

FIRSTPOWER

MATERIAL SAFETY DATA SHEET

SECTION I: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTITY:

No-Ox-Id Grease "A",
C&D Part Nos. RG -19, 25, 26

MANUFACTURER NAME: Sanchem, Inc.**ADDRESS:**

1600 South Canal Street
Chicago, Illinois 60616

TELEPHONE: (312) 733-6100**EMERGENCY:** (312) 733-6100**SUPPLIER NAME:** FIRSTPOWER GROUP LLC**ADDRESS:** 8941 Dutton Drive
Twinsburg, OH 44087**TELEPHONE:** 330-963-2050

SECTION II: COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENT

	CAS#	OSHA PEL	ACGIH TLV	% BY WEIGHT
Petroleum Wax	64742-61-6	N/A	N/A	85%
Light Napthenic Oil	64741-52-2	N/A	N/A	15%

SECTION 313 (40 CFR 372) LISTED TOXIC CHEMICALS ARE PRECEDED BY AN *.

SECTION III: HAZARDS IDENTIFICATION

Rating Codes

0=Insignificant

1=Slight

2=Moderate

3=High

4=Extreme

HMIS RATING

Health: 0

Reactivity: 1

Flammability: 0

Other: 0

NFPA RATING

Health: 0

Reactivity: 1

Flammability: 0

Other: 0

SECTION IV: FIRST AID MEASURES

Skin Contact: May cause minor skin irritation. Wash well with soap and water.

Eye Contact: Flush with water for 15 minutes, consult a Physician.

Ingestion: Induce vomiting, seek medical attention immediately.

SECTION V: FIREFIGHTING MEASURES**FIRE AND EXPLOSIVE PROPERTIES:**

Flash Point: 450 F (C. O. C.)

EXTINGUISHING MEDIA: Dry Chemical, Sand or Foam

Flammable Limits LEL: 0.9% **UEL:** 6.0%

SPECIAL FIREFIGHTING PROCEDURES: None

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION VI: ACCIDENTAL RELEASE MEASURES

DOES NOT APPLY

SECTION VII: HANDLING AND STORAGE**PRECAUTIONS FOR SAFE HANDLING AND USE:**

If material is spilled: Scoop up spill and store in sealed drums, wash spill area with detergent and water.

STORAGE: Store in cool, dry area away from flames, sparks and oxidizers.

SECTION VIII: EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION: N/A

RESPIRATORY PROTECTION: Not Required

EYE WEAR: Safety Goggles

GLOVES: Rubber

WORK PRACTICES: Wash hands before eating.

OTHER PROTECTIVE CLOTHING: Not Required

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 450 F

SPECIFIC GRAVITY: (Water = 1)0.86

MELTING POINT: 140 - 150 F

VAPOR PRESSURE: N/A

EVAPORATION RATE: NA

VAPOR DENSITY: N/A

SOLUBILITY: (Water : Insoluble)**APPEARANCE / ODOR:** dark brown firm grease, odorless

SECTION X: STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Open Flame or Excessive Heat

INCOMPATIBILITY: (Material to avoid) Strong oxidizers

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: None

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION XI: TOXICOLOGICAL INFORMATION

CARCINOGENICITY: None known at this time

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None Known

SECTION XII: ECOLOGICAL INFORMATION

NOT APPLICABLE

SECTION XIII: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Incineration or reclaim Consult Federal, State and Local regulations.

RCRA Waste Disposal No.: N/A

SECTION XIV: TRANSPORT INFORMATION

NOT APPLICABLE

SECTION XV: REGULATORY INFORMATION

NOT APPLICABLE

SECTION XVI: OTHER INFORMATION

The information herein is given in good faith, but no warranty, expressed or implied is made.